

# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

## 1 Identification

- **Product identifier**
- **Trade name:** Original Satin Finish
- **Article number:** TB 6044
- **Recommended use and restriction on use**
- **Recommended use:** Coating compound/ Surface coating/ paint
- **Restrictions on use:** No further relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
Waterlox Coatings Corporation  
9808 Meech Avenue  
CLEVELAND, OH 44105  
(216) 641-4877
- **Emergency telephone number:**  
ChemTel Inc.  
(800)255-3924, +1 (813)248-0585

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Additional information:**

There are no other hazards not otherwise classified that have been identified.

0 percent of the mixture consists of ingredient(s) of unknown toxicity.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Original Satin Finish

(Contd. of page 1)

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Stoddard solvent  
 Distillates (petroleum), hydrotreated light  
 Naphthenic acids, cobalt salts  
 2-butanone oxime  
 Rosin

- **Hazard statements**


H226 Flammable liquid and vapor.  
 H317 May cause an allergic skin reaction.  
 H351 Suspected of causing cancer.  
 H361 Suspected of damaging fertility or the unborn child.  
 H372 Causes damage to the central nervous system through prolonged or repeated exposure.  
 H304 May be fatal if swallowed and enters airways.

- **Precautionary statements**

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P210 Keep away from heat, sparks, open flames, and hot surfaces. - No smoking.  
 P260 Do not breathe mist/vapors/spray.  
 P264 Wash thoroughly after handling.  
 P280 Wear protective gloves/protective clothing/eye protection.  
 P233 Keep container tightly closed.  
 P270 Do not eat, drink or smoke when using this product.  
 P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.  
 P363 Wash contaminated clothing before reuse.  
 P308+P313 IF exposed or concerned: Get medical advice/attention.  
 P331 Do NOT induce vomiting.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2  
 Fire = 2  
 Reactivity = 0

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Original Satin Finish

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**


















HEALTH	2	Health = *2
FIRE	2	Fire = 2
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

8052-41-3	Stoddard solvent  Flam. Liq. 3, H226  STOT RE 1, H372; Asp. Tox. 1, H304	50-100%
64742-47-8	Distillates (petroleum), hydrotreated light  Asp. Tox. 1, H304	10-25%
8001-26-1	Linseed oil	≤ 2.5%
96-29-7	2-butanone oxime  Carc. 2, H351  Eye Dam. 1, H318  Acute Tox. 4, H312; Skin Sens. 1, H317 Flam. Liq. 4, H227	≤ 2.5%
8050-09-7	Rosin  Skin Sens. 1, H317	≤ 2.5%
136-51-6	calcium bis(2-ethylhexanoate)  Repr. 2, H361  Eye Dam. 1, H318	≤ 2.5%
100-41-4	ethylbenzene  Flam. Liq. 2, H225  Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304  Acute Tox. 4, H332	≤ 2.5%
61789-51-3	Naphthenic acids, cobalt salts  Carc. 2, H351; Repr. 2, H361  Skin Sens. 1, H317	≤ 2.5%
98-54-4	4-tert-butylphenol  Repr. 2, H361  Eye Dam. 1, H318  Skin Irrit. 2, H315	≤ 2.5%

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

**Trade name: Original Satin Finish**

(Contd. of page 3)

· **Additional information:**

For the listed ingredient(s), the identity and exact percentage(s) are being withheld as a trade secret.

## 4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation is experienced, consult a doctor.

· **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

A person vomiting while lying on their back should be turned onto their side.

Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

Headache

Breathing difficulty

Coughing

Dizziness

Cramp

Nausea

Disorientation

· **Danger**

Danger of impaired breathing.

Danger of convulsion.

Danger of disturbed cardiac rhythm.

Vapours may cause drowsiness and dizziness.

· **Indication of any immediate medical attention and special treatment needed**

Monitor circulation, possible shock treatment.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary edema.

If swallowed or in case of vomiting, danger of entering the lungs.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

**Trade name: Original Satin Finish**

(Contd. of page 4)

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
  - Foam
  - Fire-extinguishing powder
  - Gaseous extinguishing agents
  - Carbon dioxide
  - Water fog / haze
- **For safety reasons unsuitable extinguishing agents:**
  - Water spray
  - Water stream.
- **Special hazards arising from the substance or mixture**
  - Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**
  - Wear self-contained respiratory protective device.
  - Wear fully protective suit.
- **Additional information**
  - Eliminate all ignition sources if safe to do so.
  - Cool endangered receptacles with water fog.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
  - Use respiratory protective device against the effects of fumes/dust/aerosol.
  - Wear protective equipment. Keep unprotected persons away.
  - Ensure adequate ventilation.
  - Keep away from ignition sources.
  - Protect from heat.
  - Particular danger of slipping on leaked/spilled product.
- **Environmental precautions:**
  - Do not allow to enter sewers/ surface or ground water.
  - Prevent from spreading (e.g. by damming-in or oil barriers).
- **Methods and material for containment and cleaning up:**
  - Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
  - Allow to solidify. Pick up mechanically.
  - Dispose contaminated material as waste according to item 13.
  - Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**
  - See Section 7 for information on safe handling.
  - See Section 8 for information on personal protection equipment.
  - See Section 13 for disposal information.

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Original Satin Finish

(Contd. of page 5)

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Avoid splashes or spray in enclosed areas.  
Use only in well ventilated areas.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Flammable gas-air mixtures may be formed in empty receptacles.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Provide ventilation for receptacles.  
Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**  
Store away from foodstuffs.  
Store away from oxidizing agents.
- **Further information about storage conditions:**  
Store in cool, dry conditions in well sealed receptacles.  
Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

### Components with limit values that require monitoring at the workplace:

#### 8052-41-3 Stoddard solvent

PEL (USA)	Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm
REL (USA)	Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup> *15-min
TLV (USA)	Long-term value: 525 mg/m <sup>3</sup> , 100 ppm
EL (Canada)	Short-term value: 580 mg/m <sup>3</sup> Long-term value: 290 mg/m <sup>3</sup>
EV (Canada)	Long-term value: 525 mg/m <sup>3</sup>
LMPE (Mexico)	Long-term value: 100 ppm

#### 64742-47-8 Distillates (petroleum), hydrotreated light

EL (Canada)	Long-term value: 200 mg/m <sup>3</sup> Skin
-------------	--

(Contd. on page 7)

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

**Trade name: Original Satin Finish**

(Contd. of page 6)

**8001-26-1 Linseed oil**

PEL (USA)	Short-term value: 15* 5** mg/m <sup>3</sup> *Total dust **Respirable fraction
OEL (Canada)	Short-term value: 10* 3** mg/m <sup>3</sup> *Mist **Respirable mist
TWA (Canada)	Short-term value: 10* 3** mg/m <sup>3</sup> *Mist **Respirable mist

**96-29-7 2-butanone oxime**

WEEL (USA)	Long-term value: 10 ppm DSEN
------------	---------------------------------

**8050-09-7 Rosin**

TLV (USA)	DSEN, RSEN, L
EL (Canada)	S
LMPE (Mexico)	SEN, (L)

**100-41-4 ethylbenzene**

PEL (USA)	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL (USA)	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV (USA)	Long-term value: 87 mg/m <sup>3</sup> , 20 ppm BEI
EL (Canada)	Long-term value: 20 ppm IARC 2B
EV (Canada)	Short-term value: 540 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
LMPE (Mexico)	Long-term value: 20 ppm

**· Ingredients with biological limit values:**

**100-41-4 ethylbenzene**

BEI (USA)	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Pregnant women should strictly avoid inhalation or ingestion.  
Wash hands before breaks and at the end of work.

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

**Trade name: Original Satin Finish**

(Contd. of page 7)

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- **Engineering controls:** No further relevant information available.

- **Breathing equipment:**

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when aerosol or mist is formed.

For spills, respiratory protection may be advisable.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Eye protection:**



Safety glasses

- **Body protection:** Solvent resistant protective clothing

- **Limitation and supervision of exposure into the environment**

No further relevant information available.

- **Risk management measures**

See Section 7 for additional information.

No further relevant information available.

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

<b>Form:</b>	Liquid
--------------	--------

<b>Color:</b>	Dark amber
---------------	------------

- **Odor:** Petroleum-like

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
-------------------------------------	---------------

<b>Boiling point/Boiling range:</b>	150 - 199 °C (302 - 390 °F)
-------------------------------------	-----------------------------

- **Flash point:** 38 °C (100 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Auto-ignition temperature:** Not determined.

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not self-igniting.

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Original Satin Finish

(Contd. of page 8)

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
- **Explosion limits:**
  - Lower: 0.8 Vol %
  - Upper: 6.0 Vol %
- **Vapor pressure:** Not determined.
- **Density at 20 °C (68 °F):** 0.87 g/cm<sup>3</sup> (7.26 lbs/gal)
- **Relative density:** Not determined.
- **Vapour density:** Not determined.
- **Evaporation rate:** Not determined.
- **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic: Not determined.
  - Kinematic: Not determined.
- **Other information:** No further relevant information available.

## 10 Stability and reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:**
- **Thermal decomposition / conditions to be avoided:** Avoid open flame, ignition sources, contact with incompatible substances.
- **Possibility of hazardous reactions:** Flammable.  
Toxic fumes may be released if heated above the decomposition point.  
Reacts with strong oxidizing agents.  
Used empty containers may contain product gases which form explosive mixtures with air.  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
- **Conditions to avoid:** Keep ignition sources away - Do not smoke.  
Store away from oxidizing agents.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide  
Hydrocarbons  
Nitrogen oxides (NO<sub>x</sub>)  
Toxic metal compounds

(Contd. on page 10)

# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Original Satin Finish

(Contd. of page 9)

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**
- **on the skin:** Based on available data, the classification criteria are not met.
- **on the eye:** Based on available data, the classification criteria are not met.
- **Subacute to chronic toxicity:** May be fatal if swallowed and enters airways.
- **Additional toxicological information:**
- **Carcinogenic categories**

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

- **Probable Routes of Exposure**

Ingestion.  
Inhalation.  
Eye contact.  
Skin contact.

- **Repeated Dose Toxicity:** Repeated exposures may result in skin and/or respiratory sensitivity.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**
- **Carc. 2, Repr. 2**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Suspected of causing cancer.
- **Reproductive toxicity** Suspected of damaging fertility or the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
- **Causes damage to the central nervous system through prolonged or repeated exposure.**
- **Aspiration hazard** May be fatal if swallowed and enters airways.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** The product contains materials that are harmful to the environment.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Due to mechanical actions of the product (e.g. agglutinations) damages may occur.
- **Additional ecological information:**
- **General notes:**
- **Do not allow product to reach ground water, water course or sewage system.**
- **Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.**

(Contd. on page 11)

# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Original Satin Finish

· **Other adverse effects** No further relevant information available.

(Contd. of page 10)

## 13 Disposal considerations

· **Waste treatment methods**· **Recommendation:**

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

· **Uncleaned packagings:**· **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

· **UN-Number**· **DOT, ADR, IMDG, IATA**

UN1263

· **UN proper shipping name**

Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 5 L (1.3 gal).

· **DOT, IATA**

Paint related material

· **ADR**

1263 PAINT RELATED MATERIAL

· **IMDG**

PAINT RELATED MATERIAL

· **Transport hazard class(es)**· **DOT**· **Class**

3 Flammable liquids

· **Label**

3

· **ADR**· **Class**

3 (F1) Flammable liquids

(Contd. on page 12)

# Safety Data Sheet


acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Original Satin Finish

(Contd. of page 11)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E, <u>S</u> -E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN1263, Paint related material, 3, III

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

### · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

### · Section 313 (Specific toxic chemical listings):

61789-51-3 | Naphthenic acids, cobalt salts

### · TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 13)

# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Original Satin Finish

(Contd. of page 12)

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
100-41-4	ethylbenzene	D

- **IARC (International Agency for Research on Cancer)**

7631-86-9	silicon dioxide	3
9002-88-4	Linear Low Density Polyethylene	3
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
61789-51-3	Naphthenic acids, cobalt salts	2B

- **TLV (Threshold Limit Value established by ACGIH)**

100-41-4	ethylbenzene	
----------	--------------	--

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **State Right to Know Listings**

None of the ingredients is listed.

- **Canadian substance listings:**

- **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

- **Canadian Ingredient Disclosure list (limit 0.1%)**

100-41-4	ethylbenzene	
----------	--------------	--

- **Canadian Ingredient Disclosure list (limit 1%)**

8052-41-3	Stoddard solvent	
7631-86-9	silicon dioxide	
8001-26-1	Linseed oil	

- **Other regulations, limitations and prohibitive regulations**

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 14)

# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

**Trade name: Original Satin Finish**

(Contd. of page 13)

· **Date of preparation / last revision** 07/09/2015 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Flam. Liq. 4: Flammable liquids, Hazard Category 4

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

· **Sources**

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: [www.chemtelinc.com](http://www.chemtelinc.com)