



TRUETONE[®]

BUFF-IN-COLOR FOR WOOD



Protect your wood project with the trusted, go-to finish wood enthusiasts choose.

Easily applied with buffing machine or hand buffing

Enhances wood grain and brings out its inherent beauty

Low odor, low VOC and easy to clean up

Color-infused Tung Oil available in 11 colors



FAMILY OWNED SINCE 1910



Learn more at waterlox.com/truetone

Our TRUETONE® Formula

Our TRUETONE formula enhances the color and grain of your wood with a buff-in, color-infused Tung Oil available in 11 colors. TrueTone adds rich color and water-resistant protection while being easy to maintain, low odor and VOC compliant.

PRODUCT DETAILS:

- VOC compliant in all 50 states.
- Like all of our Tung Oil formulas 90% of the resin portion of the formula is from renewable, natural resources.
- Easily applied to floors with a buffing machine or other surfaces by hand buffing.
- Penetrates and waterproofs when used as a finishing system in conjunction with Waterlox TrueTone Color-Infused Tung Oils.
- Penetrates, waterproofs and forms a protective yet elastic finish against common household spills, moisture and foot traffic.
- Easy to clean, maintain and spot repair.
- Non-toxic when dry and fully cured.
- Hand made in Ohio by a 4th generation, family-owned company.
- Will produce an unfinished look with a matte sheen.
- Available in gallon (finish only), quart, pint and 2 ounce sizes.

PRODUCT USES & TIPS:

- Use on interior wood surfaces including floors, windows, doors, cabinetry, woodwork, tables, furniture, bar tops, picture frames, and various woodworking projects.
- One gallon covers 3,200-3,800 square feet per coat. One quart covers 600-800 square feet per coat. The number of coats depends upon the porosity of the wood. No thinning necessary.
- Minimum dry time of 24 hours between coats. Poor ventilation, high humidity or cool temperatures may increase dry times.
- Once the project is completed, removing the finish can be very difficult as Waterlox will alter the appearance of porous substrates. Apply all intended coats to a small, inconspicuous area or scrap piece of substrate from the project and allow to dry properly prior to the actual application. Final color effect is always influenced by the texture, porosity, and by the method of application and will be difficult to reverse once finished.

- 1 First, apply one of these products to add color to your wood surface.

TRUETONE COLOR-INFUSED TUNG OIL

PRODUCT #: **TB 7000-7010**

This is a buff-in-color product and should be used under the Waterlox TRUETONE Buff-In Tung Oil Finish product (TB 7011).



Ebony	Classic Gray	Ash
Frost	Clay	Red Mahogany
Chestnut	Nutmeg	Natural
White	Pickled White	

All colors here are digital representations. Final colors may vary based on wood selection.

- 2 Second, apply this product to create a protective finish.

TRUETONE BUFF-IN TUNG OIL FINISH

PRODUCT #: **TB 7011**

ORIGINAL

PRODUCT #: **TB 5284, TB 3182 and TB 6044**

H2OLOX

PRODUCT #: **TB 2000, TB 2001, TB 2002 and TB 2003**

URETHANE

PRODUCT #: **TB 4252, TB 5824 and TB 5930**

MARINE

PRODUCT #: **TB 3940 and TB 6032**

These products are finishes and should be used as the 2nd and 3rd coats over the Waterlox TRUETONE Color-Infused Tung Oil products (TB 7000-7010).

Premium tung oil finishes since 1910.