



MARINE

OUTDOOR FINISH MADE WITH RESIN-MODIFIED TUNG OIL



Protect your wood project with the trusted,
go-to finish wood enthusiasts choose.

Easy to apply,
maintain
and restore

Enhances wood
grain and brings out its
inherent beauty

Protects against
UV rays, harsh weather
and moisture

Available in
satin and gloss
sheens



FAMILY
OWNED
SINCE 1910



Learn more at waterlox.com/marine

Our MARINE Formula

Our MARINE formula preserves the beauty and integrity of outdoor and marine wood. Our resin-modified Tung Oil products form a protective and elastic finish against sun/UV rays, harsh weather and moisture exposure.

PRODUCT DETAILS:

- Like all of our Tung Oil formulas 90% of the resin portion of the formula is from renewable, natural resources.
- When used in conjunction with a Waterlox sealer, our MARINE formula penetrates deep into wood fibers to create a waterproof barrier while forming a protective yet elastic film that is durable against sun/UV rays, harsh weather and moisture exposure.
- Easier to maintain than other exterior clear or surface finishes.
- Non-toxic when dry and fully cured.
- Hand made in Ohio by a 4th generation, family-owned company.
- Available in gloss and satin sheens.
- Available in gallon, quart and 2 ounce sizes.

PRODUCT USES & TIPS:

- For use on exterior surfaces in direct sunlight/UV.
- Specially made for boat decks, bright work, spars and other heavy-duty exterior applications, such as exterior doors and garage doors in direct sunlight/UV.
- Not recommended for use on pressure-treated woods or exterior walking surfaces in direct sunlight, such as an architectural deck.
- One quart of MARINE sealer or finish covers 125 square feet per coat (500 square feet per coat for one gallon). One quart of the Universal Tung Oil Sealer covers 600-800 square feet per coat. No thinning required.
- Minimum dry time of 24 hours between coats. Poor ventilation, high humidity or cool temperatures may increase dry times.

1 First, apply ONE OF THESE products to create a waterproof seal.

MARINE SEALER

OR

UNIVERSAL TUNG OIL SEALER

PRODUCT #:
TB 3809



PRODUCT #:
TB 1000



2 Second, apply one of these products to build a protective and elastic finish.

MARINE GLOSS FINISH

PRODUCT #: **TB 3940**
GLOSS LEVEL: **90-95°**

This product is a finish and should be used as the 2nd and 3rd coats over the Waterlox Universal Tung Oil Sealer (TB 1000).



MARINE SATIN FINISH

PRODUCT #: **TB 6032**
GLOSS LEVEL: **30-40°**

This product is a finish and should be used as the 2nd and 3rd coats over the Waterlox Universal Tung Oil Sealer (TB 1000).



Premium tung oil finishes since 1910.