

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Marine Finish Satin
- **Article number:** TB 6032
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Coating compound/ Surface coating/ paint
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Waterlox Coatings Corporation
9808 Meech Avenue
CLEVELAND, OH 44105
(216) 641-4877
- **1.4 Emergency telephone number:**
ChemTel Inc.
(800)255-3924, +1 (813)248-0585

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.
Classifications listed also are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).
The following Hazard Statements are applicable only according to OSHA regulations within the United States. These Statements are not applicable for the CLP regulation (1272/2008/EC) in the EU: H351, H361.



Repr. 2 H361: Suspected of damaging fertility or the unborn child.

Carc. 2 H351: Suspected of causing cancer.



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



corrosion

Eye Dam. 1 H318 Causes serious eye damage.

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Marine Finish Satin

(Contd. of page 1)



Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

Xn; Harmful

R65: Harmful: may cause lung damage if swallowed.

Xn; Sensitising

R42/43: May cause sensitisation by inhalation and skin contact.

Xi; Irritant

R41: Risk of serious damage to eyes.

R10-52/53: Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· **Additional information:**

There are no other hazards not otherwise classified that have been identified.

0 percent of the mixture consists of component(s) of unknown toxicity

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is additionally classified and labelled according to the Globally Harmonized System within the United States (GHS).

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS05 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

Stoddard solvent

phthalic anhydride

Distillates (petroleum), hydrotreated light

Naphthenic acids, cobalt salts

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Marine Finish Satin

(Contd. of page 2)

2-butanone oxime

· **Hazard statements**

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.

The following Hazard Statements are applicable only according to OSHA regulations within the United States. These Statements are not applicable for the CLP regulation (1272/2008/EC) in the EU: H351, H361.

H351: Suspected of causing cancer.

H361: Suspected of damaging fertility or the unborn child.

H226 Flammable liquid and vapour.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

The following Precautionary Statements are applicable only to the OSHA GHS regulations and not the specific CLP regulation: P201, P202, P308+P313.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P285 In case of inadequate ventilation wear respiratory protection.

P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves / eye protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P363 Wash contaminated clothing before reuse.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P331 Do NOT induce vomiting.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Hazard description:**

· **WHMIS-symbols:**

B2 - Flammable liquid

D2A - Very toxic material causing other toxic effects



· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Marine Finish Satin

(Contd. of page 3)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = *2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

Warning: Contains lead salt(s). Long-term health hazard.

* - Indicates a long term health hazard from repeated or prolonged exposures.

· **HMIS Long Term Health Hazard Substances**

96-29-7	2-butanone oxime
61789-51-3	Naphthenic acids, cobalt salts
98-54-4	4-tert-butylphenol

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 8052-41-3 EINECS: 232-489-3 Index number: 649-345-00-4	Stoddard solvent ☒ Xn R65 R10 ----- ☠ Flam. Liq. 3, H226 ☠ Asp. Tox. 1, H304	25-50%
CAS: 64742-47-8 EINECS: 265-149-8 Index number: 649-422-00-2	Distillates (petroleum), hydrotreated light ☒ Xn R65 ☠ Asp. Tox. 1, H304	10-25%
CAS: 85-44-9 EINECS: 201-607-5 Index number: 607-009-00-4	phthalic anhydride ☒ Xn R22; ☒ Xn R42/43; ☒ Xi R37/38-41 ☠ Resp. Sens. 1, H334 ☠ Eye Dam. 1, H318 ☠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	2,5-10%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9	xylene ☒ Xn R20/21; ☒ Xi R38 R10 ----- ☠ Flam. Liq. 3, H226 ☠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2,5-10%

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Marine Finish Satin

(Contd. of page 4)

CAS: 56-81-5 EINECS: 200-289-5	glycerol substance with a Community workplace exposure limit	≤ 2,5%
CAS: 96-29-7 EINECS: 202-496-6 Index number: 616-014-00-0	2-butanone oxime ☒ Xn R21-40; ☒ Xi R41; ☒ Xi R43 Carc. Cat. 3 ----- ☠ Carc. 2, H351 ☞ Eye Dam. 1, H318 ☠ Acute Tox. 4, H312; Skin Sens. 1, H317	< 1%
CAS: 98-54-4 EINECS: 202-679-0	4-tert-butylphenol ☒ Xn R62; ☒ Xi R38-41; ☠ N R51/53 Repr. Cat. 3 ----- ☠ Repr. 2, H361f ☞ Eye Dam. 1, H318 ☠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 ☠ Skin Irrit. 2, H315	< 1%
CAS: 61789-51-3 EINECS: 263-064-0	Naphthenic acids, cobalt salts ☒ Xn R62; ☒ Xi R43; ☠ N R51/53 Repr. Cat. 3 ----- ☠ Repr. 2, H361f ☠ Skin Sens. 1, H317 Aquatic Chronic 3, H412	< 1%

· **Additional information:**

For the listed ingredients, the identity and exact percentages are being withheld as a trade secret.
For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

· **After inhalation:**

Supply fresh air and to be sure to call for a doctor.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Protect unharmed eye.

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Marine Finish Satin

(Contd. of page 5)

- **After swallowing:**
Rinse out mouth and then drink plenty of water.
Do not induce vomiting; call for medical help immediately.
A person vomiting while laying on their back should be turned onto their side.
- **4.2 Most important symptoms and effects, both acute and delayed**
Asthma attacks
Headache
Breathing difficulty
Allergic reactions
Coughing
Dizziness
Nausea
Strong irritant with the danger of severe eye injury.
- **Hazards**
May cause respiratory irritation.
Danger of impaired breathing.
Causes serious eye damage.
Danger of disturbed cardiac rhythm.
Danger of convulsion.
Vapours may cause drowsiness and dizziness.
- **4.3 Indication of any immediate medical attention and special treatment needed**
If swallowed or in case of vomiting, danger of entering the lungs.
Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.
Later observation for pneumonia and pulmonary oedema.
Medical supervision for at least 48 hours.
Monitor circulation, possible shock treatment.
If necessary oxygen respiration treatment.
Treat skin and mucous membrane with antihistamine and corticoid preparations.
Contains phthalic anhydride. May produce an allergic reaction.
In cases of irritation to the lungs, initial treatment with cortical steroid inhalants.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Foam
Fire-extinguishing powder
Gaseous extinguishing agents
Carbon dioxide
Water haze or fog
- **For safety reasons unsuitable extinguishing agents:**
Water spray
Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Marine Finish Satin

(Contd. of page 6)

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

· **Additional information**

Eliminate all ignition sources if safe to do so.

Cool endangered receptacles with water fog or haze.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Protect from heat.

Isolate area and prevent access.

Particular danger of slipping on leaked/spilled product.

· **6.2 Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers).

· **6.3 Methods and material for containment and cleaning up:**

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Allow to solidify. Pick up mechanically.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Send for recovery or disposal in suitable receptacles.

Used rags or other cleaning materials should be soaked with water and placed in a sealed container.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

Rags / metal wools / cuttings / shavings and waste papers soaked with product must be placed in a sealed, metal container rated for flammable waste.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Flammable gas-air mixtures may form in empty receptacles.

Keep respiratory protective device available.

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Marine Finish Satin

(Contd. of page 7)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Provide ventilation for receptacles.
Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidizers, strong acids, strong bases.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:

8052-41-3 Stoddard solvent

PEL (USA)	Long-term value: 2900 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 350 mg/m ³ Ceiling limit: 1800* mg/m ³ *15-min
TLV (USA)	Long-term value: 525 mg/m ³ , 100 ppm
EL (Canada)	Short-term value: 580 mg/m ³ Long-term value: 290 mg/m ³
EV (Canada)	Long-term value: 525 mg/m ³

64742-47-8 Distillates (petroleum), hydrotreated light

EL (Canada)	Long-term value: 200 mg/m ³ Skin
-------------	--

1330-20-7 xylene

IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin
PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Marine Finish Satin

(Contd. of page 8)

EL (Canada)	Short-term value: 150 ppm Long-term value: 100 ppm
EV (Canada)	Short-term value: 650 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
56-81-5 glycerol	
PEL (USA)	Long-term value: 15* 5** mg/m ³ mist; *total dust **respirable fraction
TLV (USA)	TLV withdrawn-insufficient data human occup. exp.
EL (Canada)	Long-term value: 10* 3** mg/m ³ *mist; **mist, resirable
EV (Canada)	Long-term value: 10 mg/m ³
96-29-7 2-butanone oxime	
WEEL (USA)	Long-term value: 10 ppm DSEN

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.

· **Ingredients with biological limit values:**

1330-20-7 xylene

BEI (USA)	1,5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

- **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Pregnant women should strictly avoid inhalation or ingestion.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Respiratory protection:**



Combined Organic Vapor and Particulate Respirator is recommended for use during all processing activities.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Marine Finish Satin

(Contd. of page 9)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**

Contact lenses should not be worn.



Safety glasses

- **Body protection:** Solvent resistant protective clothing

- **Limitation and supervision of exposure into the environment**

No further relevant information available.

- **Risk management measures**

See Section 7 for additional information.

No further relevant information available.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Colour: Amber coloured

- **Odour:** Petroleum-like

- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Not Determined.

Boiling point/Boiling range: 140 - 199 °C (284 - 390 °F)

- **Flash point:** 35 °C (95 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Auto/Self-ignition temperature:** Not determined.

- **Decomposition temperature:** Not determined.

- **Self-igniting:** Product is not self-igniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Marine Finish Satin

(Contd. of page 10)

- **Explosion limits:**
 - Lower:** 0,8 Vol %
 - Upper:** 7,0 Vol %
- **Vapour pressure at 20 °C (68 °F):** 2 hPa (2 mm Hg)
- **Density at 20 °C (68 °F):** 0,87 g/cm³ (7,26 lbs/gal)
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
Avoid open flame, ignition sources, contact with incompatible substances.
- **10.3 Possibility of hazardous reactions**
Flammable.
Reacts with strong acids and oxidising agents.
Reacts with strong alkali.
Used empty containers may contain product gases which form explosive mixtures with air.
Toxic fumes may be released if heated above the decomposition point.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
- **10.4 Conditions to avoid**
Keep ignition sources away - Do not smoke.
Store away from oxidising agents.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Hydrocarbons
Toxic metal compounds

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values relevant for classification:** None.

(Contd. on page 12)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Marine Finish Satin

(Contd. of page 11)

- **Primary irritant effect:**
- **on the skin:** Slight irritant effect on skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitisation:** Sensitising effect by skin contact is possible by prolonged exposure.
- **Subacute to chronic toxicity:** May be fatal if swallowed and enters airways.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant
Danger through skin adsorption.
Toxic and/or corrosive effects may be delayed up to 24 hours.
- **Acute effects (acute toxicity, irritation and corrosivity):** May be harmful if inhaled.
- **Repeated dose toxicity:**
May cause damage to organs through prolonged or repeated exposure.
Repeated exposures may result in skin and/or respiratory sensitivity.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**
Carc. 2B
Classification for the United States only.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** The material is harmful to the environment.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

(Contd. on page 13)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Marine Finish Satin

(Contd. of page 12)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number

DOT, ADR, IMDG, IATA

UN1263

14.2 UN proper shipping name



Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 5 L (1.3 gal).

DOT, IATA

Paint related material

ADR

1263 PAINT RELATED MATERIAL

IMDG

PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

DOT



Class

3 Flammable liquids.

Label

3

ADR



Class

3 (F1) Flammable liquids.

Label

3

(Contd. on page 14)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Marine Finish Satin

(Contd. of page 13)

· IMDG, IATA



- Class 3 Flammable liquids.
- Label 3
- 14.4 Packing group
- DOT, ADR, IMDG, IATA III
- 14.5 Environmental hazards:
- Marine pollutant: No
- 14.6 Special precautions for user Warning: Flammable liquids.
- Danger code (Kemler): 30
- EMS Number: F-E, S-E
- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.
- Transport/Additional information:

· ADR

- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- Transport category 3
- Tunnel restriction code D/E

· IMDG

- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- UN "Model Regulation": UN1263, PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

85-44-9	phthalic anhydride
1330-20-7	xylene
61789-51-3	Naphthenic acids, cobalt salts

(Contd. on page 15)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Marine Finish Satin

(Contd. of page 14)

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65 (California):**

· **Chemicals known to cause cancer:**

Present in trace quantities.

1317-36-8	lead monoxide
100-41-4	ethylbenzene
91-20-3	naphthalene
50-00-0	formaldehyde

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic Categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
71-36-3	butan-1-ol	D

· **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
9003-07-0	polypropylene glycol diglycidyl ether	3
61789-51-3	Naphthenic acids, cobalt salts	2B

· **TLV (Threshold Limit Value established by ACGIH)**

85-44-9	phthalic anhydride	A4
1330-20-7	xylene	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

· **Canada**

· **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**

85-44-9	phthalic anhydride
---------	--------------------

· **Canadian Ingredient Disclosure list (limit 1%)**

8052-41-3	Stoddard solvent
-----------	------------------

· **Other regulations, limitations and prohibitive regulations**

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

(Contd. on page 16)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Marine Finish Satin

(Contd. of page 15)

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients are listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H361f Suspected of damaging fertility.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- R10 Flammable.
- R20/21 Harmful by inhalation and in contact with skin.
- R21 Harmful in contact with skin.
- R22 Harmful if swallowed.
- R37/38 Irritating to respiratory system and skin.
- R38 Irritating to skin.
- R40 Limited evidence of a carcinogenic effect.
- R41 Risk of serious damage to eyes.
- R42/43 May cause sensitisation by inhalation and skin contact.
- R43 May cause sensitisation by skin contact.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R62 Possible risk of impaired fertility.
- R65 Harmful: may cause lung damage if swallowed.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 17)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Marine Finish Satin

(Contd. of page 16)

NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Flam. Liq. 3: Flammable liquids, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Carc. 2: Carcinogenicity, Hazard Category 2
Repr. 2: Reproductive toxicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com