

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Waterlox Original Marine Sealer
- **Article number:** TB 3809
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Coating compound/ Surface coating/ paint
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Waterlox Coatings Corporation
9808 Meech Avenue
CLEVELAND, OH 44105
(216) 641-4877
- **1.4 Emergency telephone number:**
ChemTel Inc.
(800)255-3924, +1 (813)248-0585

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Classifications listed also are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).
The following classifications are applicable only to OSHA (USA) regulations and not the specific CLP regulation: H317, H351, H361.



Repr. 2 H361: Suspected of damaging fertility or the unborn child.

Carc. 2 H351: Suspected of causing cancer.



Skin Sens. 1 H317: May cause an allergic skin reaction.



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Harmful

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Waterlox Original Marine Sealer

(Contd. of page 1)

R65: Harmful: may cause lung damage if swallowed.

R10: Flammable.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· **Additional information:**

There are no other hazards not otherwise classified that have been identified.

0 percent of the mixture consists of component(s) of unknown toxicity

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is additionally classified and labelled according to the Globally Harmonized System within the United States (GHS).

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

Stoddard solvent

2-butanone oxime

Naphthenic acids, cobalt salts

Rosin

· **Hazard statements**

The following Hazard Statements are applicable only according to OSHA regulations within the United States. These Statements are not applicable for the CLP regulation (1272/2008/EC) in the EU: H317, H351, H361.

H317: May cause an allergic skin reaction.

H351: Suspected of causing cancer.

H361: Suspected of damaging fertility or the unborn child.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

The following Precautionary Statements are applicable only to the OSHA GHS regulations and not the specific CLP regulation: P201, P202, P308+P313.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Waterlox Original Marine Sealer

(Contd. of page 2)

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.
 P363 Wash contaminated clothing before reuse.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P331 Do NOT induce vomiting.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

EUH208 Contains Naphthenic acids, cobalt salts, 2-butanone oxime, Rosin. May produce an allergic reaction.

· **Hazard description:**

· **WHMIS-symbols:**

B3 - Combustible liquid

D2A - Very toxic material causing other toxic effects



· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **HMIS Long Term Health Hazard Substances**

96-29-7	2-butanone oxime
136-51-6	calcium bis(2-ethylhexanoate)

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: **Waterlox Original Marine Sealer**

(Contd. of page 3)

Dangerous components:

CAS: 8052-41-3 EINECS: 232-489-3 Index number: 649-345-00-4	Stoddard solvent ☒ Xn R65 R10 ☠ Flam. Liq. 3, H226 ☠ Asp. Tox. 1, H304	50-100%
CAS: 8050-09-7 EINECS: 232-475-7 Index number: 650-015-00-7	Rosin ☒ Xi R43 ☠ Skin Sens. 1, H317	< 1%
CAS: 61789-51-3 EINECS: 263-064-0	Naphthenic acids, cobalt salts ☒ Xn R62; ☒ Xi R43; ☠ N R51/53 Repr. Cat. 3 ☠ Repr. 2, H361f ☠ Skin Sens. 1, H317 Aquatic Chronic 3, H412	< 1%
CAS: 96-29-7 EINECS: 202-496-6 Index number: 616-014-00-0	2-butanone oxime ☒ Xn R21-40; ☒ Xi R41; ☒ Xi R43 Carc. Cat. 3 ☠ Carc. 2, H351 ☠ Eye Dam. 1, H318 ☠ Acute Tox. 4, H312; Skin Sens. 1, H317	< 1%
CAS: 136-51-6 EINECS: 205-249-0	calcium bis(2-ethylhexanoate) ☒ Xn R63; ☒ Xi R41 Repr. Cat. 3 ☠ Repr. 2, H361d ☠ Eye Dam. 1, H318	< 1%

Additional information:

For the listed ingredients, the identity and exact percentages are being withheld as a trade secret.
For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Waterlox Original Marine Sealer

(Contd. of page 4)

If skin irritation is experienced, consult a doctor.

· **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

A person vomiting while laying on their back should be turned onto their side.

· **4.2 Most important symptoms and effects, both acute and delayed**

Headache

Allergic reactions

Dizziness

Coughing

Breathing difficulty

Nausea

Cramp

Disorientation

· **Hazards**

Danger of impaired breathing.

Danger of convulsion.

Danger of disturbed cardiac rhythm.

Vapours may cause drowsiness and dizziness.

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

If swallowed or in case of vomiting, danger of entering the lungs.

Monitor circulation, possible shock treatment.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary oedema.

Medical supervision for at least 48 hours.

Contains Naphthenic acids, cobalt salts, 2-butanone oxime, Rosin. May produce an allergic reaction.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

Foam

Fire-extinguishing powder

Gaseous extinguishing agents

Carbon dioxide

Water haze or fog

· **For safety reasons unsuitable extinguishing agents:**

Water spray

Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Waterlox Original Marine Sealer

(Contd. of page 5)

- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information**
Eliminate all ignition sources if safe to do so.
Cool endangered receptacles with water fog or haze.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
Protect from heat.
Particular danger of slipping on leaked/spilled product.
- **6.2 Environmental precautions:**
Do not allow to enter sewers/ surface or ground water.
Prevent from spreading (e.g. by damming-in or oil barriers).
- **6.3 Methods and material for containment and cleaning up:**
Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
Allow to solidify. Pick up mechanically.
Send for recovery or disposal in suitable receptacles.
Dispose contaminated material as waste according to item 13.
Used rags or other cleaning materials should be soaked with water and placed in a sealed container.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Avoid splashes or spray in enclosed areas.
Rags / metal wools / cuttings / shavings and waste papers soaked with product must be placed in a sealed, metal container rated for flammable waste.
Use only in well ventilated areas.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
Flammable gas-air mixtures may form in empty receptacles.

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Waterlox Original Marine Sealer

(Contd. of page 6)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Provide ventilation for receptacles.
Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidising agents.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Store receptacle in a well ventilated area.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:

8052-41-3 Stoddard solvent

PEL (USA)	Long-term value: 2900 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 350 mg/m ³ Ceiling limit: 1800* mg/m ³ *15-min
TLV (USA)	Long-term value: 525 mg/m ³ , 100 ppm
EL (Canada)	Short-term value: 580 mg/m ³ Long-term value: 290 mg/m ³
EV (Canada)	Long-term value: 525 mg/m ³

8050-09-7 Rosin

TLV (USA)	DSEN, RSEN, L
EL (Canada)	S

96-29-7 2-butanone oxime

WEEL (USA)	Long-term value: 10 ppm DSEN
------------	---------------------------------

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.
- **Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
Avoid contact with the eyes and skin.
Immediately remove all soiled and contaminated clothing.
Keep away from foodstuffs, beverages and feed.

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Waterlox Original Marine Sealer

(Contd. of page 7)

Pregnant women should strictly avoid inhalation or ingestion.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· **Respiratory protection:**

Suitable respiratory protective device recommended.

Use suitable respiratory protective device when high concentrations are present.

Use suitable respiratory protective device when aerosol or mist is formed.

For spills, respiratory protection may be advisable.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses

· **Body protection:** Solvent resistant protective clothing

· **Limitation and supervision of exposure into the environment**

No further relevant information available.

· **Risk management measures**

See Section 7 for additional information.

No further relevant information available.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Liquid

Colour:

Dark Amber

· **Odour:**

Petroleum-like

· **Odour threshold:**

Not determined.

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Waterlox Original Marine Sealer

(Contd. of page 8)

· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Not Determined.
Boiling point/Boiling range:	105 - 199 °C (221 - 390 °F)
· Flash point:	38 °C (100 °F)
· Flammability (solid, gaseous):	Not applicable.
· Auto/Self-ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not self-igniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0,8 Vol %
Upper:	6,0 Vol %
· Vapour pressure:	Not determined.
· Density at 20 °C (68 °F):	0,83 g/cm ³ (6,926 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
Avoid open flame, ignition sources, contact with incompatible substances.
- **10.3 Possibility of hazardous reactions**
Flammable.
Develops readily flammable gases/fumes.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
Reacts with strong oxidising agents.
Toxic fumes may be released if heated above the decomposition point.
Used empty containers may contain product gases which form explosive mixtures with air.

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Waterlox Original Marine Sealer

(Contd. of page 9)

- **10.4 Conditions to avoid**
Keep ignition sources away - Do not smoke.
Store away from oxidising agents.
- **10.5 Incompatible materials:** Oxidizing agents
- **10.6 Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Nitrogen oxides (NO_x)
Hydrocarbons
Toxic metal compounds

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values relevant for classification:** None.
- **Primary irritant effect:**
- **on the skin:** Slight irritant effect on skin and mucous membranes.
- **on the eye:** Slight irritant effect on eyes.
- **Sensitisation:** Sensitising effect by skin contact is possible by prolonged exposure.
- **Subacute to chronic toxicity:** May be fatal if swallowed and enters airways.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Toxic and/or corrosive effects may be delayed up to 24 hours.
- **Repeated dose toxicity:**
May cause damage to organs through prolonged or repeated exposure.
Repeated exposures may result in skin and/or respiratory sensitivity.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**
Carc. 2B
Classification for the United States only.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** The product contains materials that are harmful to the environment.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Due to mechanical actions of the product (e.g. agglutinations) damages may occur.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Waterlox Original Marine Sealer

(Contd. of page 10)

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **DOT, ADR, IMDG, IATA** UN1263
- **14.2 UN proper shipping name**



Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 5 L (1.3 gal).

- **DOT, IATA** Paint related material
- **ADR** 1263 PAINT RELATED MATERIAL
- **IMDG** PAINT RELATED MATERIAL
- **14.3 Transport hazard class(es)**

- **DOT**



- **Class** 3 Flammable liquids.
- **Label** 3

(Contd. on page 12)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Waterlox Original Marine Sealer

(Contd. of page 11)

· ADR



· Class 3 (F1) Flammable liquids.
· Label 3

· IMDG, IATA



· Class 3 Flammable liquids.
· Label 3
· 14.4 Packing group
· DOT, ADR, IMDG, IATA III
· 14.5 Environmental hazards:
· Marine pollutant: No
· 14.6 Special precautions for user Warning: Flammable liquids.
· Danger code (Kemler): 30
· EMS Number: F-E,S-E
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
· Transport category 3
· Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation": UN1263, PAINT RELATED MATERIAL, 3, III

(Contd. on page 13)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Waterlox Original Marine Sealer

(Contd. of page 12)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

61789-51-3 Naphthenic acids, cobalt salts

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65 (California):

· Chemicals known to cause cancer:

Present in trace quantities.

50-00-0 formaldehyde

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic Categories

· EPA (Environmental Protection Agency)

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer)

61789-51-3 Naphthenic acids, cobalt salts

2B

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Canada

· Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients are listed.

· Canadian Ingredient Disclosure list (limit 1%)

8052-41-3 Stoddard solvent

(Contd. on page 14)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Waterlox Original Marine Sealer

(Contd. of page 13)

· **Other regulations, limitations and prohibitive regulations**

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients are listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
 - H304 May be fatal if swallowed and enters airways.
 - H312 Harmful in contact with skin.
 - H317 May cause an allergic skin reaction.
 - H318 Causes serious eye damage.
 - H351 Suspected of causing cancer.
 - H361d Suspected of damaging the unborn child.
 - H361f Suspected of damaging fertility.
 - H412 Harmful to aquatic life with long lasting effects.
-
- R10 Flammable.
 - R21 Harmful in contact with skin.
 - R40 Limited evidence of a carcinogenic effect.
 - R41 Risk of serious damage to eyes.
 - R43 May cause sensitisation by skin contact.
 - R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 - R62 Possible risk of impaired fertility.
 - R63 Possible risk of harm to the unborn child.
 - R65 Harmful: may cause lung damage if swallowed.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 WHMIS: Workplace Hazardous Materials Information System (Canada)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 Flam. Liq. 3: Flammable liquids, Hazard Category 3

(Contd. on page 15)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: Waterlox Original Marine Sealer

(Contd. of page 14)

Acute Tox. 4: Acute toxicity, Hazard Category 4
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Carc. 2: Carcinogenicity, Hazard Category 2
Repr. 2: Reproductive toxicity, Hazard Category 2
Repr. 2: Reproductive toxicity, Hazard Category 2
Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com