



TRUETONE[®]

BUFF-IN-COLOR FOR WOOD | MADE WITH TUNG OIL



Protect your wood project with the trusted,
go-to finish wood enthusiasts choose.

Easily applied with
buffing machine or
hand buffing

Enhances wood
grain and brings out its
inherent beauty

Low odor,
low VOC and
easy to clean up

Color-infused
Tung Oil available in
11 colors



FAMILY
OWNED
SINCE 1910



Learn more at waterlox.com/truetone

Our TRUETONE® Formula

Our TRUETONE formula enhances the color and grain of your wood with a buff-in, color-infused Tung Oil available in 11 colors. TrueTone adds rich color and water-resistant protection while being easy to maintain, low odor and VOC compliant.

PRODUCT DETAILS:

- VOC compliant in all 50 states.
- Like all of our Tung Oil formulas 90% of the resin portion of the formula is from renewable, natural resources.
- Easily applied to floors with a buffing machine or other surfaces by hand buffing.
- Penetrates and waterproofs when used as a finishing system in conjunction with Waterlox TrueTone Color-Infused Tung Oils.
- Penetrates, waterproofs and forms a protective yet elastic finish against common household spills, moisture and foot traffic.
- Easy to clean, maintain and spot repair.
- Non-toxic when dry and fully cured.
- Hand made in Ohio by a 4th generation, family-owned company.
- Will produce an unfinished look with a matte sheen.
- Available in gallon (finish only), quart, pint and 2 ounce sizes.

PRODUCT USES & TIPS:

- Use on interior wood surfaces including floors, windows, doors, cabinetry, woodwork, tables, furniture, bar tops, picture frames, and various woodworking projects.
- One gallon covers 3,200-3,800 square feet per coat. One quart covers 600-800 square feet per coat. The number of coats depends upon the porosity of the wood. No thinning necessary.
- Minimum dry time of 24 hours between coats. Poor ventilation, high humidity or cool temperatures may increase dry times.
- Once the project is completed, removing the finish can be very difficult as Waterlox will alter the appearance of porous substrates. Apply all intended coats to a small, inconspicuous area or scrap piece of substrate from the project and allow to dry properly prior to the actual application. Final color effect is always influenced by the texture, porosity, and by the method of application and will be difficult to reverse once finished.

- 1 First, apply one of these products to add color to your wood surface.

COLOR-INFUSED TUNG OIL

PRODUCT #: **TB 7000-7010**

This is a buff-in-color product and should be used under the Waterlox TRUETONE Buff-In Tung Oil Finish product (TB 7011).



Ebony

Classic Gray

Ash

Frost

Clay

Red Mahogany

Chestnut

Nutmeg

Natural

White

Pickled White

All colors here are digital representations. Final colors may vary based on wood selection.

- 2 Second, apply this product to create a protective finish.

BUFF-IN TUNG OIL FINISH

PRODUCT #: **TB 7011**

GLOSS LEVEL: **6-8°**

This product is a finish and should be used as the 2nd and 3rd coats over the Waterlox TRUETONE Color-Infused Tung Oil products (TB 7000-7010).



Premium tung oil finishes since 1910.